

Interior shielded LED ceiling luminaires
STUDIO LINE

BEGA

Application

A series of downlights featuring a velvet black housing finish and a highly efficient LED source. Their unique beauty and versatility is enhanced by the choice of three interior metal paint finishes. These stylish metal finishes can be chosen to compliment a wide array of interior decorations, as the internally reflected light takes on the quality and color of the metal paint. The result is an eye-catching, yet subtle hint of colored light on the outside edges of the beam spread.

Materials

Luminaire housing constructed of aluminum alloy
Trim constructed of aluminum with velvet black painted exterior finish and interior metal painted finish
Silicone optical lens

NRTL listed to North American Standards, suitable for damp locations
Weight: 0.7 lbs

Electrical

Operating voltage	120-277V AC
Minimum start temperature	-30° C
LED module wattage	4.9W
System wattage	6.6W
Controllability	0-10V dimmable
Color rendering index	Ra > 80
Luminaire lumens	243 lumens (3000K)
Lifetime at Ta = 15° C	> 500,000 h (L70)
Lifetime at Ta = 40° C	178,000 h (L70)

LED color temperature

- 4000K - Product number + **K4**
- 3500K - Product number + **K35**
- 3000K - Product number + **K3**
- 2700K - Product number + **K27**

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

Select the desired trim ring material finish by using appropriate code number as suffix.

Available finishes	Velvet black · Matte aluminum	Code number .2
	Velvet black · Matte brass	Code number .4
	Velvet black · Matte copper	Code number .6



Interior shielded LED ceiling luminaires · STUDIO LINE				Required wiring box
	LED	A	B	
50 184.2	4.9W	3 3/8	4 1/2	19538

Type:
BEGA Product:
Project:
Modified:

