

NOD

Features

Suspended rod
IP 20
Soft touch coated surface
360° turnable, 180° tiltable
Matte black
Up to 960lm
Up to 97 lm/W
27K, 30K, 35K
CRI > 90
L90 40,000h
direct light output
120 / 277 V universal
DIM 0-10 V 5%

Physical attributes

NOD-PDT-BL-OP- -C90-

Electrical attributes

UNV-010V-

Dimensional attributes

K

Physical attributes

A RANGE

NOD NOD

B MOUNTING

pendant PDT
black junction box cover included

C COLOR

black BL

D LENS

opal OP

E CCT

2700K	27K
3000K	30K
3500K	35K

F CRI

CRI > 90 C90

Electrical attributes

G VOLTAGE

Universal UNV

H DIMMING

0-10V 5% 010V

I OUTPUT LM DIRECT

900lm	00900L
2700K, 10W	
1000lm	01000L
3000K / 3500K, 10W	

J CIRCUIT / EM

no emergency *
* leave blank

Dimensional attributes


K PENDANT IN INCH

39" pre-cut	PL39IN
78" pre-cut	PL78IN

Technical data

	SIZE	LED TYPE	LED COLOR TEMPERATURE	INPUT WATTS	DELIVERED LM TOTAL	DELIVERED LM DIRECT	LIGHT DISTRIBUTION	OPTICAL EFFICIENCY	LUMINAIRE EFFICACY
	9 13/16"	e ² LED	27 K 30 K, 35 K	10 W 10 W	890 lm 960 lm	890 lm 950 lm	100 % down	80 %	90 lm/W 97 lm/W

Light distribution



Features

